ALCOLOCK™ L series

Alcohol Ignition Interlock Solutions

Available through:



ALCOLOCK USA

5776 Hoffner Avenue, Suite 303 Orlando, FL 32822

1 866 700 9300

alcolockusa.com

Quality management certifications











Warranty

All ACS alcohol ignition interlocks are warranted to be free from defects in workmanship and material for one year from the date of purchase. Only qualified technicians should perform maintenance on any alcohol ignition interlock.

ACS, ALCOHOL COUNTERMEASURE SYSTEMS, AlcoFleet, ALCOLOCK, ALCOSIM, FOCUS and the "Molly" are trademarks of Alcohol Countermeasure Systems (International) Inc. and are used under license.









ALCOLOCK L series alcohol ignition interlocks feature a user-friendly handset to perform breath alcohol tests and communicate with the driver, and an electronic control unit (ECU) that connects to the power and control circuits of the vehicle. Drivers use the handset to provide a breath sample, and the ECU inhibits vehicle operation if the test result is above the preset breath alcohol content (BrAC) limit.

Programmable

ALCOLOCK L series interlock settings are programmable to meet company safety policy requirements. Drivers may be tested at the beginning of their shift or at intervals throughout the day.

Communication capabilities

All L series devices can manually transfer data for real-time reporting of critical events, ALCOLOCK L series can be equipped with GPRS connectivity to provide instant notifications of any violations and test results.

Other models provide full-featured alcohol interlock support with close-range transmission capabilities, such as Bluetooth® and Wi-Fi®, with optional GPS integration.

Fleet monitoring solutions

L series interlocks can be integrated with existing telematics systems, recording details of the date, time, and breath test result for each event, as well as optional information such as GPS location and driver's photo.

| | Bluetooth® | Wi-Fi | GPS | GPRS | Camera | Integration with telematics |
|----|------------|----------|----------------------------------|----------|----------|-----------------------------|
| LT | | | | | optional | optional |
| LC | ✓ | optional | optional (will include Wi-Fi) | | optional | ✓ |
| LM | | | √ | √ | ✓ | |

If driver monitoring is preferred rather than blocking the vehicle starting mechanism, L Connect is a handset-only solution specially designed for direct integration into telematics systems and taxi meters.

Secure data handling

Events are logged in both the handset and the ECU, which can be downloaded remotely and accessed through a central database via AlcoFleet™ software. Data transfer is also possible via cable through a download station. Event log files and communication are protected with AES 128 bit encryption standard for security of the memory and the transmission of data files.

Attempts to tamper with the ECU or its installation into the vehicle may still be detected and recorded in the memory of the ECU with the handset disconnected. Flash memory preserves the event log when the vehicle battery is disconnected.

Optional security measures

FOCUS™ camera integrates with L series to take an image of the driver at the time of the test. The device triggers the mounted camera to provide positive identification each time

mounted camera to provide positive identification each time a breath sample is given, storing the time-stamped image.

GPS integration with ALCOLOCK L series ECUs records the coordinates of the location at which the breath test was performed.

Quality engineering

Engineered to withstand the rigors of the vehicle environment, including dust, vibration, humidity and extreme temperature. Manufactured according to IATF 16949 quality standards and conformity of ISO 9001, ISO 14001, ISO 17034 and ISO/IEC 17025 norms.



Sensor

Dual, electrochemical sensor



Specificity

Alcohol only; no response to ketones or hydrocarbons



Range of measurement 0 to 0.500 g/dL



Analysis time 5 to 15 seconds



Recycle time 5 to 10 seconds



Accuracy

± 0.005 @ 0.05 g/dL



Display OLED



Wireless options GPS and GPRS



Operating temperature -40 °F to +185 °F





Operating voltage 12 or 24 volt DC



Calibration

ALCOSIM[™] breath alcohol simulator or equivalent



Dimensions

5.5 in x 2.0 in x 1.0 in



Weight

3.7 ounces



Certification CENELEC EN 50436 parts 1 and 2